



## BESTWAY IN-GROUND LIFTS

These heavy-duty, smooth operating air/hydraulic (air over oil) motorcycle lifts can be rotated 360° and incorporate a choice of 5" or 6-1/2" diameter pistons. Lifting capacity is 1,200 lbs. for 5" and 1,800 lbs. for 6-1/2" pistons, at 125 psi air pressure.

All units are easily installed in a minimum amount of space and require a 56" deep hole. Minimum height is 3"; maximum rise above floor is 36"; (48" optional rise available). All units come complete with a three-way air valve – simply attach your air-line to operate.

### Air/Hydraulic lifts with platform

The platform on each of the three lifts in the table below is large enough to contact both bike tires, and each platform is hinged toward the rear. The first two lifts have a slideable front plate which can extend the platform to a maximum of 76". The third lift does not have a slideable front plate and is a fixed platform length of 92".



### IN-GROUND LIFT

Catalog No. 106HA-24H

(Hinged platform allows easy removal of rear wheel)

### Air/Hydraulic lifts without platform (Frame Contact)

For Harley-Davidson and other motorcycles that allow frame contact, a special version is available in either 5" or 6-1/2" piston diameters (Catalog No's. 5SPCH & 6SPCH) with a pre-drilled top designed to secure the motorcycle frame directly to the top of the lift with "J" bolts. Additional hole in plate provides access to bottom of engine.

Bestway lifts are also available "topless" so you can add a top plate of your own design (Catalog No's. 5SP & 6SP). You can also add a platform of your own to the 5SPC & 6SPC lifts by welding or bolting the platform to the 1/4" thick steel plate provided.

Catalog No.	Piston Diameter	Platform Length	Platform Width	Capacity
106HA-24H	6-1/2"	76"	24"	1800 lbs.
106HA-30H	6-1/2"	76"	30"	1800 lbs.
106HA-30XL	6-1/2"	92"	30"	1800 lbs.



### FRAME CONTACT IN-GROUND LIFT

Catalog No. 6SPCH

### Catalog No. CH-PH

Additional Top Plate Choice for Harley-Davidson  
18" x 18" plus 6" ramps\*

Catalog No.	Piston Diameter	Top Plate Dimensions	Application	Capacity
5SP	5"	N/A	Add your platform	1200 lbs.
5SPC	5"	18" x 18"	Harley-Davidson service	1200 lbs.
5SPCH	5"	18" x 18"*	Harley-Davidson service	1200 lbs.
6SP	6-1/2"	N/A	Add your platform	1800 lbs.
6SPC	6-1/2"	18" x 18"	Harley-Davidson service	1800 lbs.
6SPCH	6-1/2"	18" x 18"*	Harley-Davidson service	1800 lbs.

\*Each lift is supplied standard with air valve mounted on side as shown. Other options include a remote control air valve that allows you to locate the valve anywhere in your shop and an optional non-rotating feature that eliminates the lift from spinning. Phone The Carlson Company for details if a "remote control" or "non-rotating" feature is desired.

