

DELTRAN BATTERY CHARGERS

TEN BANK BATTERY CHARGER

Catalog No. 021-0134



FIVE BANK BATTERY CHARGER

Catalog No. 021-0133

SPECIFICATIONS

- **CHARGING PER OUTPUT:** 12V @ 2.0 Amps 72 Hour Safety Timer
- **FIVE BANK DIMENSIONS:** 8" x 6" x 6"
- **TEN BANK DIMENSIONS:** 16" x 6" x 6"

OPTIONS

- **081-0148-25** 25' extra long leads for 5 & 10 Bank Chargers
- **081-0148-25** 25' extra long leads for BG4 (4 PACK) 5 & 10 Bank Chargers

Charge multiple batteries automatically—and fast!

FEATURES

- **Safe, No Spark Charging:** Microchip circuitry won't activate voltage output until clips are correctly connected to battery.
- **4-Step Charging** (initialization, bulk charge, absorption mode, float/maintenance)
- **Automatic Storage Mode:** Charger automatically switches to a "Storage" charging (or float) mode when the battery reaches full charge
- **Multiple Battery Charging:** Lights for each set of leads indicate which batteries are "Charging" and which are in the "Storage" mode.
- **Constant Current Charging:** Provides faster charging per battery than conventional chargers
- **Automatic 12-volt charging:** No Controls

FERRET CHARGING SYSTEM/BATTERY LOAD TESTER

Load test batteries and charging systems efficiently!

This versatile volts-amps-load tester is made especially for troubleshooting electric power systems on motorcycles and other powersports vehicles. The reliable carbon pile adjusts load smoothly with less than one turn of the knob. The clip-on inductive amp probe/digital ammeter permits convenient measuring of charging system output, starter draw and battery load. A built-in direct connect milliammeter is provided for smaller draws. It's great for measuring component draw and for finding small battery drains.



SPECIFICATIONS

DIGITAL MEASUREMENT RANGES AND DIMENSIONS:

- **VOLTS:** 0.01 to 20
- **INDUCTIVE AMPS:** Plus or minus 200
- **MILLIAMPS:** Plus or minus 2000
- **WELDED STEEL CASE SIZE:** 10" x 16.5" x 9.5"

CHARGING SYSTEM/BATTERY LOAD TESTER

Catalog No. 40

Includes: Tester Stand with large wheels



FEATURES

- **4-Step Charging** (initialization, bulk charge, absorption mode, float maintenance)
- **Spark Proof**
- **Temperature Compensated**
- **Short Circuit & Reverse Polarity Protected**

BATTERY TENDER PLUS

Catalog No. 021-0128 (12V @ 1.25A)

Catalog No. 021-0144 (6V @ 1.25A)

FEATURES

- **Durable Design:** Welded steel case with powder coated finish
- **Convenient Diagnostics:** Troubleshoot high-resistance connections and read low-power sensor outputs with accurate, easy to use digital voltmeter
- **Inductive Ammeter:** Dual range ammeter lets you switch between high capacity 600 amp range and a high resolution 200 amp range.
- **Milliammeter:** Built-in direct connect milliammeter measures from 1-2000 milliamps
- **Amps Ripple Lamp:** Find bad diodes or open stator windings in alternators with the ripple detector.
- **Leads:** Sturdy battery load leads are jacketed for tangle-free handling (6 ft.)
- **Tester Stand:** Portable stand (included), offers tool storage and secures the tester at a convenient height with two quick-release latches.

