



## JAK-LIFT • LIFT GATE CRATE LIFT SHOP DOLLY

Not your ordinary JAK-LIFT, this heavy-duty portable frame contact lift operates with a foot operated pump mechanism. It is suitable for lifting most H-D style motorcycles to a height of 18-1/2" and boasts a 1200 lb. capacity. Only 4" high in the down position. Many dealers buy these for bike displaying purposes and resale to their customers.



**JAK-LIFT 360**  
Catalog No. 14279

### SPECIFICATIONS

- 4-ton Hydraulic Jack
- 2 locking positions: 11-3/4" & 18-1/2"
- 16" x 13" support platform
- 4 locking swivel wheels

8



### WINCH & CABLE

Catalog No. MC9952  
(Optional)

This Lift Gate allows you to suspend either end of almost any type of vehicle including motorcycles, ATV's, personal watercraft and snowmobiles. (Note: unit will not work on full dressed touring motorcycles.) It can be used as a stand-alone unit. It is constructed of 1.68" tubing and features three tie down points to secure the vehicle being serviced.



Motorcycle Lift Gate with Snowmobile

### OPTIONS & SPECIFICATIONS

- MC9952 Optional Winch & Cable (recommended)
- 79.5" height, 29.5" width at base

### MOTORCYCLE LIFT GATE

Catalog No. MC9940

(Shown with optional MC9952 Winch and Cable)



### MOTORCYCLE CRATE LIFT

Catalog No. MC360

A versatile shop tool that allows one person to safely remove a motorcycle out of its shipping crate for assembly. Allows operator to lift up to three times their own weight to a max. of 900 lbs. The crate lift can also be used for tire changing, fairing repairs, and front-end suspension overhaul. Features four tie-down attachment points for added safety.



### SHOP DOLLY

Catalog No. MC460

The MC460 Shop Dolly allows bikes to be easily moved around the shop and also offers a sturdy and stable way to store motorcycles and ATV's waiting for parts. Works with MC450 & MC455 Center Lift Jack and custom lift type jacks.



### FEATURES

- Adjustable width from 13" to 20" at base
- Adjustable height from 12" to 15"
- Four tie-down attachment points
- Rubber pads at frame contact points
- 1,200 lb. Capacity

